


EmCORE-i2305

Intel® Atom™ Processor E3800 Family & Celeron® Processor
3.5" Compact Board



Features

- Support Intel® Atom™ Processor E3800 family and Celeron® Processor
- Dual Gigabit Ethernet Ports
- LVDS, Analog RGB Port, HDMI port
- Support Dual Independent Displays
- Soldered Onboard eMMC (OEM request) (E3800 Family SKU Only)
- **Extended Operating Temp.: -20 ~ 70°C**
- **Wide Range Operating Temp.: -40 ~ 85°C (WT series)**

System

Processor	Soldered onboard Intel® Atom™ Processor E3800 family E3825 1.33GHz/ E3845 1.91GHz or Intel® Celeron® processor N2807 1.58GHz/ N2930 1.83GHz
Memory	1 x DDR3L SO-DIMM socket, supporting up to 8GB 1333/1660 MT/s SDRAM
BIOS	Insyde BIOS
Watchdog Timer	1~255 levels reset

I/O

Super IO Chipset	Fintek F71869ED
Serial Port	1 x RS-232 1 x RS-232/485 selectable
Keyboard & Mouse	6-pin wafer connector for PS/2 keyboard/ mouse via Y-cable
USB 2.0	4 x USB 2.0 ports
USB 3.0/2.0	1 x USB 3.0/2.0 ports 1 x Mini-card socket
Expansion	1 x micro-SDXC socket 2 x I2C ports (OEM request, E3800 family Processor only)
Storage	1 x Serial ATA ports with 300MB/s HDD transfer rate 1 x mSATA socket 4GB/ 8GB/ 16GB eMMC 4.5 (OEM request, E3800 family Processor only)
Ethernet Chipset	2 x Realtek® RTL8111 PCIe GbE controllers
Digital I/O	8-bit Programmable
Audio Interface	Realtek® ALC662 5.1 Channel HD Audio CODEC, Mic-in/ Line-in/ Line-out

Display

Graphic Chipset	Integrated Intel® HD Graphics Analog RGB with resolution up to 2048x1536, HDMI
Graphic Interface	LVDS: Dual Channels 24-bit LVDS, with resolution up to 1920x1200


OS Support

Windows 7 32/64-bit, Windows 8.1 32/64-bit
Linux: Ubuntu

Mechanical & Environmental

Power Input	DC 12V
Power Consumption	0.56A@+12V with E3825 (Typical) 0.65A@+12V with E3845 (Typical)
Operating Temp.	-20 ~ 70°C (-4 ~ 158°F) -40 ~ 85°C (-40 ~ 185°F, WT-series)
Operating Humidity	10 ~ 95% @ 70°C (non-condensing) 10 ~ 95% @ 85°C (non-condensing, WT-series)
Dimension (L x W)	146 x 102 mm (5.7" x 4.0")


Dimensions



Unit: mm



Block Diagram



Ordering Information

EmCORE-i2305-E3825	Intel® Atom™ Processor E3825 3.5" compact board
EmCORE-i2305-E3845	Intel® Atom™ Processor E3845 3.5" compact board
EmCORE-i2305-N2807(OEM request)	Intel® Celeron® Processor N2807 3.5" compact board
EmCORE-i2305-N2930(OEM request)	Intel® Celeron® Processor N2930 3.5" compact board
EmCORE-i2305-WT-E3825(BTO)	Intel® Atom™ Processor E3825 WT 3.5" compact board
EmCORE-i2305-WT-E3845(BTO)	Intel® Atom™ Processor E3845 WT 3.5" compact board

Optional Accessories

CBK-07-2305-00	Cable kit 1 x Audio cable 2 x Serial port latching cables 1 x KB/MS latching Y-cable 1 x SATA cable 1 x SATA power cable 1 x USB cable
----------------	--