




ACP-5212

21.5" Fanless Multi-Touch Computer with Onboard Intel® Dual Core Atom™ D510 Processor, 1 GB RAM



Features

- 21.5" WXGA (1366 x 768) Fanless TFT LCD Display
- Onboard Intel® Dual Core Atom™ D510 Processor
- Easy-To-Clean: Multi-Touch Window Design (Two-Point)
- IP65 Front Bezel & IPx1 Back Chassis
- Anti-Scratch Surface (7H Hardness)
- Smart Card Reader/ MSR/ Camera Support (Optional)




Specifications

System	
Processor	Onboard Intel® Dual Core Atom™ D510, 1.66 GHz
System Memory	DDR2 SODIMM x 1, up to 2 GB, Default: 1 GB
LCD/CRT Controller	Integrated in Processor
Ethernet	10/100/1000Base-TX, RJ-45 x 2
I/O Port	RS-232 x 1, RS-232/422/485 x 1, USB2.0 x 6 (2 on side; 4 on rear), Line-out x 1, VGA x 1
Storage Disk Drive	2.5" SATA Hard Disk Drive x 1/ CompactFlash™ Slot (Internal) x 1
Expansion Slot	Mini-Card x 2
OS support	Windows® XP (T/S: Single point), Linux Fedora (T/S: Multi-point), Windows® 7 (T/S: Multi-point)
Mechanical	
Construction	IP65/ NEMA4 for plastic front bezel, IPx1 for plastic chassis
Mounting	VESA 75/100
Dimension	21.5" x 13.7" x 2.34" (546mm x 348mm x 59.4mm)
Carton Dimension	26" x 19.52" x 7.87" (661mm x 496mm x 200mm)
Gross Weight	18.3 lb (8.3 Kg)
Net Weight	14.57 lb (6.61 Kg)
Environmental	
Operating Temperature	32°F ~ 104°F (0°C ~ 40°C)
Storage Temperature	-4°F ~ 158°F (-20°C ~ 70°C)
Storage Humidity	10%~95% @ 40°C; non-condensing
Vibration	1 g rms/ 5~500Hz/ Random operation (HDD)
Shock	20 G peak acceleration (11 msec. Duration)
EMC	CE/FCC Class A
Power Supply	
DC input 70W	DC 12V, with AC power adapter with lock (in package)
LCD	
Display Type	21.5" TFT-LCD, LED
Max. Resolution	1920 x 1080
Max. Colors	16.7M colors (6/8-bit for R,G,B)
Luminance	250 cd/m ²
Viewing Angle	170°(H), 160°(V)
Back Light	LED
Back Light MTBF (hours)	30,000
Touchscreen	
Type	Projected Capacitive Multi-Touch (Windows® 7)
Light Transmission	>88%

ACP-5212

Dimension

Unit: mm



Ordering Information

Part Number	Display Type	Max. Resolution	Luminance	View Angle	Backlight MTBF (Hours)	CPU	LAN	USB	RS-232	RS-485/422/232	Storage	RAM	Display	Expansion	Mounting	Power	Temp.	Touch
TF-ACP-5212HTT-A1-1012	21.5" TFT-LCD	1920 x 1080	250 cd/m ²	170(H), 160V	30,000	Intel® Atom™ D510, 1.66 GHz	2	6	1	1	CF Kit x 1 SATA-HDD Kit x 1	1 GB	VGA x 1	Mini-Card x 1	VESA 75/100	DC 12V	0°C ~ 40°C (w/o air)	Projective Capacitive Multi-Touch (Two points)

Packing List

- HDD Screws
- VESA Screws
- Anti-drop Kits
- Power Adapter
- Product DVD
- ACP-5212

Optional Accessories

- **1702031802**
Power Cord (US Type)
- **1702031803**
Power Cord (European Type)
- **170203180E**
Power Cord (Japanese Type)
- **9761518200**
Smart Card Reader
- **9761518201**
Camera
- **9761518206**
MSR + Mounting Kit
- **9761518205**
Scanner (2D) + Mounting Kit
- **P005212000**
Plastic Cover for Cables
- **ARM-WK075-0**
Wallmount Kit
- **9761215303**
Wireless Module (b/g/n)
- **9761518209**
RFID Module (13.56MHz)
- **PER-M20**
Desktop Stand w/VESA 75/100

If you want to install more than 2 optional accessories, you have to disable one USB port. Please check with your representative if needed.