

MEDDP-515

15" Slim Medical LCD Monitor



CE FC



Features

- 15" LCD Panel with LED Backlight
- Compact and Terse Design
- Wide View Angle 160°(H)/150°(V)
- VGA x 1, DVI x1
- 5 wire resistive touch screen
- Low Power Consumption

Specifications

Display

| | |
|-----------------------------|--|
| Size | 15" |
| Resolution | 1024 x 768 |
| Max. Colors | 16.2M |
| Brightness (Typ.) | 450 nits |
| Viewing Angle (CR=10)(Typ.) | 160°(H)/150°(V) |
| Contrast Ratio (Typ.) | 800:1 |
| Touch Screen | 5 wire resistive touch screen (optional) |

System

| | |
|---------------|--------------------------------------|
| OS Support | Windows® XP, Windows® 7, Windows® 10 |
| DICOM Support | Optional |

I/O

| | |
|-------------|------------------------------|
| Audio | Audio-in x 1 |
| Serial Port | USB x 1 for touch controller |
| Signal | VGA x 1, DVI x 1 |
| Speaker | 1W speaker x 1 on back side |

Mechanical and Environmental

| | |
|-------------------------------|------------------------------|
| Power Consumption | Full Loading :22.8Watts |
| Power Requirement | DC12V / 5A power input |
| Operating Temperature | 5°C ~ 40°C(41°F ~ 104°F) |
| Storage Temperature | -10°C ~ 60°C(14°F ~ 140°F) |
| Storage Humidity | 10%~90%@35°C, non-condensing |
| Gross Weight | 4.0kg (8.82lb) |
| Net Weight | 3.2kg (7.05lb) |
| Dimension | 347 x 276 x 45.2 mm |
| Package Dimension (W x D x H) | 410 x 420 x 140mm |

Certifications

CE: EN 60601-1-2:2007(V3.0) ,
EN 60601-1:2006/A1:2013/A12:2014(V3.1)
FCC: Part 18 Class B, Part 15 Class B
IEC 60601-1: 2012 (V3.1)
CCC

Ordering Information

- » **MEDDP-515ANN-A1-1010**
15" LCD Monitor, 350 nits, VGAX1,DVI x1, DC 12V Adapter
- » **MEDDP-515ARN-A1-1010**
15" LCD Monitor, 350 nits, Resistive Touch, VGAX1,DVI x1, DC 12V Adapter
- » **MEDDP-515TND-A1-1010 (DICOM)**
15" LCD Monitor, 350 nits, VGAX1.HDMIx1.DPx1, DC 12V Adapter, DICOM Function
- » **MEDDP-515TRD-A1-1010 (DICOM)**
15" LCD Monitor, 350 nits, Resistive Touch, VGAX1.HDMIx1.DPx1, DC 12V Adapter, DICOM Function